About Product

IDEA generator sets are designed to be used as backup or continuous power supply. They are subjected to detailed load and performance tests in our production facilities in order to provide ideal performance and safe usage.



Power Output Values


Voltage	Standby Power (ESP)			Prime Power (PRP)		
	kVA	kW	Ampere	kVA	kW	Ampere
400/231	**1650 kVA**	1320 kW	2384	**1500 kVA**	1200 kW	2167

Standby Power (ESP) : This rating is for the supply of continuous electrical power at variable load , in the event of utility power failure. No overload is permitted.


Prime Power (PRP) : This rating is for the supply of continuous electrical power at variable load. There is no limitation on the annual hours in operation and 10% overload power can be supplied for 1 hour in 12.

Weight And Dimensions

Type	Width x Length x Height (mm)	Weight (kg)	Fuel Tank (Lt)	Sound dB(A) @1mt
Open	2400x5900x2450 mm	10280 kg	2000 lt	-
Soundproofed	2400x7250x2750 mm	15130 kg	2000 lt	91








Engine

Frequency		50 Hz
Output Rating	kW	1450
Manufacturer and Model		Baudouin 12M33G1650/5
Fuel		Diesel
Injection		Direct
Aspiration		Turbocharged and Aftercooled
Cylinders		12 V
Bore and Stroke	mm	150 x 185
Displacement	lt	39,2
Cooling		Water
Engine Oil Specification		SAE 15W40
Compression Ratio		15:1
Engine Oil Capacity(Sump Only)	lt	155
Coolant Capacity (incl.radiator)	lt	188
Governor		ECU
Air Filter		Dry element
FUEL CONSUMPTION		
100 % Load	lt/h	324
75 % Load	lt/h	234,2
50 % Load	lt/h	156,1
EXHAUST SYSTEM		
Maximum Temperature	°C	700
Exhaust Gas Flow	m^3/min	334,9
Maximum Exhaust Back Pressure	mBar	75
Exhaust Flange Size (Internal Dia.)	mm	220
AIR SYSTEM		
Intake Air Flow	m^3/min	101,1
Air Intake Temperature Rise	°C	<5
STARTING SYSTEM		
Starter Motor	kW	2X8,5
Battery Capacity	Ah	4x220
Auxiliary Voltage	V	24

Alternator

Poles	4 pole
Winding Connections	Star
Insulation	Class H
Enclosure	IP23
Exciter System	Self regulating Brushless
Voltage Regulator	AVR
Steady State Voltage Regulation	± 1 %
Bearing	Single bearing sealed
Coupling	Flexible disc
Cooling	Direct drive centrifugal blower fan

Control Panel IDP300



The new IDP300 genset controller is a cost effective modular genset controller ready for internet monitoring through plug-in modules.

Its main advantages are multifunctionality, support for multiple topologies, harmonic analysis and detailed power measurements.

Software features are complete with easy firmware upgrade through USB port. The Windows based PC software allows monitoring and programming through USB, RS-485, RS-232, Ethernet and GPRS.

The Rainbow Scada web service allows monitoring and control of an unlimited number of gensets from a single central location.

Optional Equipments

Some Optional Equipment IDEA Provides with Generator Sets;

- Remote radiator applications,
- Automatic fuel filling system,
- Fuel tank, oil pan, instrument panel, alternator, coil heaters,
- Synchronization systems,
- Generator output fuse,
- Mains generator transfer switches,
- Seismic solutions,
- Remote monitoring
- Other requested solutions

Reference Standards

IDEA Generator Sets are CE approved and comply with the following standards;

- Power according to ISO 3046 and ISO 8528
- EN 12100 , EN 13857 , EN 60204
- 2006/42/CE Machinery Safety
- 2006/95/EC Low Voltage
- 2004/108/CE EMC
- Ambient reference conditions 1000 mbar, 25 °C, 30 % relative humidity ISO8528

All the information in this leaflet is intended for general purposes only. IDEA reserves the right to change the specifications without notice.