About Product

IDEA generator sets are designed to be used as backup or continuous power supply. They are subjected to detailed load and performance tests in our production facilities in order to provide ideal performance and safe usage.



Power Output Values


Voltage	Standby Power (ESP)			Prime Power (PRP)		
	kVA	kW	Ampere	kVA	kW	Ampere
400/231	**550 kVA**	440 kW	795	**500 kVA**	400 kW	722,5

Standby Power (ESP) : This rating is for the supply of continuous electrical power at variable load , in the event of utility power failure. No overload is permitted.


Prime Power (PRP) : This rating is for the supply of continuous electrical power at variable load. There is no limitation on the annual hours in operation and 10% overload power can be supplied for 1 hour in 12.

Weight And Dimensions

Type	Width x Length x Height (mm)	Weight (kg)	Fuel Tank (Lt)	Sound dB(A) @1mt
Open	1300x3200x2160 mm	3580 kg	600 lt	TBA
Soundproofed	1300x4910x2420 mm	4620 kg	600 lt	81







Engine


Perkins®

Frequency		50 Hz
Output Rating	kW	495
Manufacturer and Model		Perkins 2506A-E15TAG2
Fuel		Diesel
Injection		Direct
Aspiration		Turbocharged & Aftercooled
Cylinders		6
Bore and Stroke	mm	137 x 171
Displacement	lt	15,2
Cooling		Water
Engine Oil Specification		SAE 15W40
Compression Ratio		16:1
Engine Oil Capacity	lt	62
Coolant Capacity (incl.radiator)	lt	58
Governor		Electronical
Air Filter		Dry element
FUEL CONSUMPTION		
100 % Load	lt/h	100
75 % Load	lt/h	76
50 % Load	lt/h	53
EXHAUST SYSTEM		
Maximum Temperature	°C	550
Exhaust Gas Flow	m^3/min	98
Maximum Allowed Back Pressure	kPA	6,8
Exhaust Flange Size (Internal Dia.)	mm	127
AIR SYSTEM		
Intake Air Flow	m^3/min	36,6
Total Cooling Air Flow	m^3/min	722
STARTING SYSTEM		
Starter Motor	kW	7,5
Battery Capacity	Ah	2x120
Auxiliary Voltage	V	24

Alternator

Poles	4 pole
Winding Connections	Star
Insulation	Class H
Enclosure	IP23
Exciter System	Self regulating Brushless
Voltage Regulator	AVR
Steady State Voltage Regulation	± 1 %
Bearing	Single bearing sealed
Coupling	Flexible disc
Cooling	Direct drive centrifugal blower fan

Control Panel IDP300



The new IDP300 genset controller is a cost effective modular genset controller ready for internet monitoring through plug-in modules.

Its main advantages are multifunctionality, support for multiple topologies, harmonic analysis and detailed power measurements.

Software features are complete with easy firmware upgrade through USB port. The Windows based PC software allows monitoring and programming through USB, RS-485, RS-232, Ethernet and GPRS.

The Rainbow Scada web service allows monitoring and control of an unlimited number of gensets from a single central location.

Optional Equipments

Some Optional Equipment IDEA Provides with Generator Sets;

- Remote radiator applications,
- Automatic fuel filling system,
- Fuel tank, oil pan, instrument panel, alternator, coil heaters,
- Synchronization systems,
- Generator output fuse,
- Mains generator transfer switches,
- Seismic solutions,
- Remote monitoring
- Other requested solutions

Reference Standards

IDEA Generator Sets are CE approved and comply with the following standards;

- Power according to ISO 3046 and ISO 8528
- EN 12100 , EN 13857 , EN 60204
- 2006/42/CE Machinery Safety
- 2006/95/EC Low Voltage
- 2004/108/CE EMC
- Ambient reference conditions 1000 mbar, 25 °C, 30 % relative humidity ISO8528

All the information in this leaflet is intended for general purposes only. IDEA reserves the right to change the specifications without notice.